

US009680414B1

(12) United States Patent

Chen et al.

(10) Patent No.: US 9,680,414 B1

(45) **Date of Patent: Jun. 13, 2017**

(54) FREQUENCY AND AMPLITUDE STABILIZATION IN MEMS AND NEMS OSCILLATORS

(71) Applicant: **UCHICAGO ARGONNE, LLC**, Chicago, IL (US)

(72) Inventors: Changyao Chen, Wilmette, IL (US);
Omar Daniel Lopez, Chicago, IL (US);
David A. Czaplewski, Naperville, IL

(US)

(73) Assignee: UCHICAGO ARGONNE, LLC,

Chicago, IL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 15/042,912

(22) Filed: Feb. 12, 2016

(51) Int. Cl.

H03B 5/30 (2006.01)

H03L 7/00 (2006.01)

H03K 5/003 (2006.01)

H03K 5/13 (2014.01)

B81B 7/02 (2006.01)

H03G 3/20 (2006.01)

H03K 5/00 (2006.01)

 USPC 74/490.1, 490.09; 330/137; 331/154, 96, 331/116 M, 158, 107 A See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

6,763,340	B1	7/2004	Burns et al.
7,552,645	B2	6/2009	Bargatin et al.
8,063,535	B2	11/2011	Mohanty et al.
8,836,444	B2	9/2014	Lopez et al.
9,000,833	B2	4/2015	Caffee et al.
2006/0061425	A1*	3/2006	Arigliano H03K 5/1565
			331/36 C
2014/0266509	A1	9/2014	Caffee et al.
2015/0177272	A1	6/2015	Clark

* cited by examiner

Primary Examiner — Arnold Kinkead

(74) Attorney, Agent, or Firm — Foley & Lardner LLP

(57) ABSTRACT

This invention comprises a nonlinear micro- and nanomechanical resonator that can maintain frequency of operation and amplitude of operation for a period of time after all external power has been removed from the device. Utilizing specific nonlinear dynamics of the micromechanical resonator, mechanical energy at low frequencies can be input and stored in higher frequencies modes, thus using the multiple degrees of freedom of the resonator to extend its energy storage capacity. Furthermore, the energy stored in multiple vibrational modes can be used to maintain the resonator oscillating for a fixed period of time, even without an external power supply. This is the first demonstration of an "autonomous" frequency source that can maintain a constant frequency and vibrating amplitude when no external power is provided, making it ideal for applications requiring an oscillator in low power, or limited and intermittent power supplies.

20 Claims, 7 Drawing Sheets

